

# **Epson Series UV** Roll to Roll Printer

3.2米UV卷材打印机 — 高性价比之选

Dual Heads 双喷头

4/5-Color

4/5色写真

Variable Dot

可变墨滴

White Optional

白色可选

Epson Official Supplied i3200-U Printheads 配备爱普生官方原装i3200-U喷头





**PRECISION CORE** PRINTHEAD i3200-U powered by EPSON

## UV Roll to Roll Printer

## **UV-1260S**

#### • Features 特点



**Epson Official Supplied Printheads** Latest Epson Industrial Printhead i3200-U Equipped. Focus on super fast speed printing.

最新的爱普生i3200-U工业级喷头,专注高速打印



#### Water Cooling UV-LED Lamp

It is one of the world's top UV-LED, long lifespan, low heat, and instant on-off

装备世界顶级的UV-LED,寿命长,发热低,即时开关



#### Variable Dot Print Technology

Permitting the printer to provide smooth gradations, exceptional solid colors and optimum image quality in all print modes

使打印画面的颜色过渡更加自然,实现高质量成像



#### Anti-collision Function

Anti-collision system is equipped to protect the printhead and carriage all the time

标配防撞装置,支持中断处续打



#### Advanced Media Handling

With SinoColor advanced movement control system, each pass is uniform allowing for more sellable output in less time

儒彩先进的收放布控制系统,提高生产效率

- ★ High-density UV curable ink produces rich, vibrant colors on coated or uncoated media 高密度UV固化墨水在涂层或非涂层材料上实现丰富而鲜明的色彩
- ★ Durable, scratch-resistant and virtually odorless, more than three years outdoor durability without lamination

画面持久, 耐刮擦, 无异味, 不覆膜长达三年的户外耐候性

★ Branded parts are used for high attrition area. Greatly increased the lifetime and stability of the machine. For example, Hiwin guide rail, German Igus drag chain, Italian Megadyne belt.

高损耗处皆使用高等级配件,极大提升设备使用寿命和稳定性

### Sp∈cification 参数

			<u>-</u>
Model No.		型号	UV-1260S
Printing Head		打印喷头	2 × Epson i3200-U
Resolution		打印精度	2400 dpi MAX
Media 耗材	Width	耗材宽度	3200 mm MAX
	Туре	耗材种类	Canvas, Leather, PET Film, Reflective Film, Soft Ceiling Film & More Flexible Material Etc. 天花软膜、灯布、车贴、皮革、PET膜、反光膜以及其他众多卷材
Ink 墨水	Туре	墨水类型	UV Ink
	Color	墨水颜色	CMYK/CMYK+W
	Curing	墨水固化	High Quality Whater Cooling UV-LED Lamp 水冷UV-LED灯
Speed 速度	Test Color Mode		СМҮК
	Draft	草图模式	46 m²/h
	Productio	n 标准模式	34 m²/h
	Quality	精细模式	23 m²/h
Cleaning 清洗系统		清洗系统	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头
Feed & TakeUp		收放布	Automatic Media Feeding (Standard) & Take up System (Optional) 自动收放布
Rip Software		操作软件	Main Top(Standard) / Photo Print(Optional)
Connector		连接方式	USB 3.0
Power		电力消耗	AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 2000W MAX
Size 尺寸	Machine	机器尺寸	L4360 x W800 x H1270 mm
	Packing	包装尺寸	L4610 x W1000 x H740 mm
Weight 重量	Machine	机器重量	480 KG
	Packing	机器重量	640 KG

VOTE CANDIDATE