

UV Roll to Roll Printer

UR-3200R & UR-2000R

• Features 特点



Ricoh Gen5 Printhead.

It is designed with longevity and robustness in mind and widely used in many latest industrial inkjet printers.

理光Gen5打印碰头,它的设计考虑到工业使用所需 求的寿命和坚固性



Material Tension System

Tension media feeding system is standard equipped to guarantee the high accuracy of material stepping.

张力放布系统。保障高精度步进。



Negative Pressure System

Two advanced separate negative pressure systems. Simply and effectively ensure the continuous ink flow, and easy maintenance for multi-heads equipment.

配置高级的负压系统。稳定供墨,简化多头设备维护。



Dual guide rail

Dual guide rail configuration, guarantee the stability of long time running.

双导轨设计、提高设备长时间运行的稳定性



Anti-collision System

Printer will automatically stop when the carriage hit any unexpected object during working, and support continuing printing from the interruption part, reduce the material waste.

小车遇撞击自动停止, 并支持中断处续打, 减少意外带 来的材料浪费

* Well-designed tension type material feeding and take-up system. Ensure the high accuracy of material stepping.

精心设计的张力收放布系统,精确走步

- ★ Mature time-set stirring system for white ink, effectively decrease the problems caused by white ink precipitation. 成熟的白墨定时搅拌装置,有效防止UV白墨沉淀
- ★ Elegant and sleek appearance design, not only an advanced printing equipment, but also a decoration for the company. 简约大气的外观设计



● Specification 参数

Model No.		型号	UR-3200R	UR-2000R
Printing Head		打印喷头	2/3/4 Ricoh Gen5 Heads	
Resolution		打印精度	Max 1440dpi	
Media 耗材	Width	耗材宽度	3200 mm Max	2000 mm Max
	Туре	耗材种类	Canvas, Garment, Leather, PET Film, Reflective Film, Soft Ceiling Film & More Flexible Material Etc. 天花软膜、灯布、车贴、服装、皮革、PET膜、反光膜以及其他众多卷材	
Ink 墨水	Туре	墨水类型	UV Ink	
	Color	墨水颜色	CMYK/CMYK+W / CMYK+W+V	
	Curing	墨水固化	High Quality Whater Cooling UV-LED Lamp 水冷UV-LED灯	
Speed 速度	Color Mode 颜色模式		CMYK, 4 Heads	
	Draft	草图模式	30 m²/h	23 m²/h
	Productio	n 标准模式	21 m²/h	16 m²/h
	Quality	精细模式	17 m²/h	13 m²/h
Ink Supply System 供墨系统		供墨系统	Two advanced separate negative pressure systems (One for color and varnish, One for white).	
Cleaning 清洗系统		清洗系统	Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗、闪喷、封喷头	
Feed & TakeUp		收放布	Automatic Media Feeding (Standard) & Take up System (Optional) 自动收放布	
Rip Software 操作		操作软件	Photoprint	
Connector 3		连接方式	USB 3.0	
Power		电力消耗	AC 110V / 220V ± 5%, 16A, 50/60Hz ± 1, 1500W MAX	
Size 尺寸	Machine	机器尺寸	L5170 x W920 x H1710 mm	L3770 x W920 x H1710 mm
	Packing	包装尺寸	L5270 x W1020 x H1940 mm	L3870 x W1020 x H1940 mm
Weight 重量	Machine	机器重量	1000 KG	850 KG
	Packing	机器重量	1300 KG	1100 KG